

**SAFETY DATA SHEET  
CRYSTIC 356PA**

**1 IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING**

PRODUCT NAME                    CRYSTIC 356PA  
 PRODUCT NO.                    C30009  
 SUPPLIER                         Scott Bader  
     Wollaston  
     Wellingborough  
     Northamptonshire. NN29 7RL  
     +44(0)1933 663100  
     +44(0)1933 663693

**2 HAZARDS IDENTIFICATION**

Flammable. Harmful by inhalation. Irritating to eyes and skin. Limited evidence of a carcinogenic effect. Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

CLASSIFICATION                    Xn;R20. Carc 3;R40. Xi;R36/38. R10, R52/53.

**PHYSICAL AND CHEMICAL HAZARDS**

The product is flammable, and heating may generate vapours which may form explosive vapour/air mixtures.

**HUMAN HEALTH**

In high concentrations, vapours and spray mists are narcotic and may cause headache, fatigue, dizziness and nausea. Vapours/aerosol spray may irritate the respiratory system. Repeated exposure may cause skin dryness or cracking. Known or suspected carcinogen for humans.

**3 COMPOSITION/INFORMATION ON INGREDIENTS**

Name	EC No.	CAS-No.	Content	Classification
ANTIMONY TRIOXIDE	215-175-0	1309-64-4	2-4%	Carc3;R40
DIBROMO NEOPENTYL GLYCOL	221-967-7	3296-90-0	<2%	Carc 3;R40.
STYRENE	202-851-5	100-42-5	20-25%	R10 Xn;R20 Xi;R36/38
TRIS(2-CHLOROETHYL) PHOSPHATE	204-118-5	115-96-8	2-4%	Carc3;R40 Xn;R22 N;R51/53

The Full Text for all R-Phrases are Displayed in Section 16

**COMPOSITION COMMENTS**

Unsaturated polyester resin in reactive solvent.

**4 FIRST-AID MEASURES**

**GENERAL INFORMATION**

General first aid, rest, warmth and fresh air. Do not give victim anything to drink if they are unconscious. Get medical attention if any discomfort continues.

**INHALATION**

Place unconscious person on the side in the recovery position and ensure breathing. If respiratory problems, artificial respiration/oxygen. Get medical attention if any discomfort continues.

**INGESTION**

Immediately rinse mouth and drink plenty of water or milk. Keep person under observation. Do not induce vomiting. If vomiting occurs, keep head low. Transport immediately to hospital and take these instructions.

**SKIN CONTACT**

Use appropriate hand lotion to prevent defatting and cracking of skin. Immediately remove contaminated clothing. Wash off promptly and flush contaminated skin with water. Promptly remove clothing if soaked through and flush skin with water.

**EYE CONTACT**

Make sure to remove any contact lenses from the eyes before rinsing. Promptly wash eyes with plenty of water while lifting the eye lids. Get medical attention promptly if symptoms occur after washing.

**5 FIRE-FIGHTING MEASURES**

**EXTINGUISHING MEDIA**

Fire can be extinguished using: Water spray, fog or mist. Foam, carbon dioxide or dry powder. Dry chemicals, sand, dolomite etc. Do not use water jet as an extinguisher, as this will spread the fire.

# CRYSTIC 356PA

## SPECIAL FIRE FIGHTING PROCEDURES

Use pressurised air mask if product is involved in a fire. Cool containers exposed to flames with water until well after the fire is out. Keep run-off water out of sewers and water sources. Dike for water control.

## UNUSUAL FIRE & EXPLOSION HAZARDS

Fire causes formation of toxic gases.

## PROTECTIVE MEASURES IN FIRE

Self contained breathing apparatus and full protective clothing must be worn in case of fire.

## 6 ACCIDENTAL RELEASE MEASURES

### PERSONAL PRECAUTIONS

Wear protective clothing as described in Section 8 of this safety data sheet.

### ENVIRONMENTAL PRECAUTIONS

Spillages or uncontrolled discharges into watercourses must be IMMEDIATELY alerted to the Environmental Agency or other appropriate regulatory body.

### SPILL CLEAN UP METHODS

Keep combustibles away from spilled material. Extinguish all ignition sources. Avoid sparks, flames, heat and smoking. Ventilate. Absorb in vermiculite, dry sand or earth and place into containers. Wash thoroughly after dealing with a spillage.

## 7 HANDLING AND STORAGE

### USAGE PRECAUTIONS

Keep away from heat, sparks and open flame. Avoid spilling, skin and eye contact. Ventilate well, avoid breathing vapours. Use approved respirator if air contamination is above accepted level. Vapours are heavier than air and may spread near ground to sources of ignition.

### STORAGE PRECAUTIONS

Flammable/combustible - Keep away from oxidisers, heat and flames. Store in tightly closed original container in a dry, cool and well-ventilated place. Keep in original container. Avoid contact with oxidising agents.

### STORAGE CLASS

Flammable liquid storage.

## 8 EXPOSURE CONTROLS/PERSONAL PROTECTION

Name	Std	LT - ppm	LT - mg/m3	ST - ppm	ST - mg/m3
STYRENE	WEL	100 ppm	430 mg/m3	250 ppm	1080 mg/m3

### INGREDIENT COMMENTS

WEL = Workplace Exposure Limits Due to the hazardous nature of ingredients, exposure should be minimal.

### PROTECTIVE EQUIPMENT



### PROCESS CONDITIONS

Provide eyewash station.

### ENGINEERING MEASURES

Provide adequate ventilation, including appropriate local extraction, to ensure that the defined workplace exposure limit is not exceeded. All handling to take place in well-ventilated area.

### RESPIRATORY EQUIPMENT

Provide adequate ventilation. Observe Workplace Exposure Limits and minimise the risk of inhalation of vapours. At work in confined or poorly ventilated spaces, respiratory protection with air supply must be used. Wear mask supplied with: Gas cartridge suitable for organic substances.

### HAND PROTECTION

For prolonged or repeated skin contact use suitable protective gloves. Use protective gloves made of: Neoprene. Nitrile. Rubber (natural, latex).

### EYE PROTECTION

Wear splash-proof eye goggles to prevent any possibility of eye contact.

### OTHER PROTECTION

Wear appropriate clothing to prevent any possibility of skin contact.

### HYGIENE MEASURES

DO NOT SMOKE IN WORK AREA! Wash at the end of each work shift and before eating, smoking and using the toilet. Promptly remove any clothing that becomes contaminated. Use appropriate skin cream to prevent drying of skin. When using do not eat, drink or smoke.

## 9 PHYSICAL AND CHEMICAL PROPERTIES

### APPEARANCE

Viscous liquid

# CRYSTIC 356PA

COLOUR	Varying
ODOUR	Solvent.
SOLUBILITY	Insoluble in water
BOILING POINT (°C)	50-150
RELATIVE DENSITY	1.10 - 1.20 25°C
FLASH POINT (°C)	32 CC (Closed cup).

## 10 STABILITY AND REACTIVITY

### STABILITY

Stable under normal temperature conditions.

### CONDITIONS TO AVOID

Avoid exposure to high temperatures or direct sunlight.

### HAZARDOUS POLYMERISATION

May polymerise.

### MATERIALS TO AVOID

Alkali metals. Strong oxidising substances. Strong acids. Strong alkalis. Organic peroxides/hydroperoxides. Inorganic peroxides.

### HAZARDOUS DECOMPOSITION PRODUCTS

Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapours.

## 11 TOXICOLOGICAL INFORMATION

### GENERAL INFORMATION

Prolonged and repeated contact with solvents over a long period may lead to permanent health problems. Organic solvents may be absorbed into the body by inhalation and ingestion and cause permanent damage to the nervous system, including the brain.

### INHALATION

In high concentrations, vapours may irritate throat and respiratory system and cause coughing. In high concentrations, vapours are narcotic and may cause headache, fatigue, dizziness and nausea. Gas or vapour is harmful on prolonged exposure or in high concentrations.

### INGESTION

Gastrointestinal symptoms, including upset stomach.

### SKIN CONTACT

Acts as a defatting agent on skin. May cause cracking of skin, and eczema. Irritating to skin. May be absorbed through the skin.

### EYE CONTACT

Irritation of eyes and mucous membranes.

### Other Health Effects

Carcinogen Category 3.

## 12 ECOLOGICAL INFORMATION

### ECOTOXICITY

Dangerous for the environment: May cause long-term adverse effects in the aquatic environment.

## 13 DISPOSAL CONSIDERATIONS

### GENERAL INFORMATION

Waste to be treated as controlled waste. Disposal to licensed waste disposal site in accordance with local Waste Disposal Authority.

### DISPOSAL METHODS

Dispose of waste and residues in accordance with local authority requirements. Make sure containers are empty before discarding (explosion risk). Absorb in vermiculite or dry sand, dispose in licensed hazardous waste.

## 14 TRANSPORT INFORMATION



UK ROAD CLASS	3
PROPER SHIPPING NAME	RESIN SOLUTION
UN NO. ROAD	1866
UK ROAD PACK GR.	III
ADR CLASS NO.	3

# CRYSTIC 356PA

ADR CLASS	Class 3: Flammable liquids.
ADR PACK GROUP	III
HAZARD No. (ADR)	30
ADR LABEL NO.	3
HAZCHEM CODE	3Y
CEPIC TEC(R) NO.	30GF1-I+II, 30GF1-sp
RID CLASS NO.	3
RID PACK GROUP	III
UN NO. SEA	1866
IMDG CLASS	3
IMDG PAGE NO.	3
IMDG PACK GR.	III
EMS	F-E, S-E
MARINE POLLUTANT	No.
UN NO. AIR	1866
AIR CLASS	3
AIR PACK GR.	III

## 15 REGULATORY INFORMATION

### LABELLING



Harmful

### CONTAINS

ANTIMONY TRIOXIDE  
DIBROMO NEOPENTYL GLYCOL  
STYRENE  
TRIS(2-CHLOROETHYL) PHOSPHATE

### RISK PHRASES

R10	Flammable.
R20	Harmful by inhalation.
R36/38	Irritating to eyes and skin.
R40	Limited evidence of a carcinogenic effect.
R52/53	Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

### SAFETY PHRASES

S24/25	Avoid contact with skin and eyes.
S26	In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
S36/37	Wear suitable protective clothing and gloves.
S51	Use only in well-ventilated areas.
S60	This material and its container must be disposed of as hazardous waste.
P5	Contains epoxy constituents. See information supplied by the manufacturer.
P14	Contains COBALT OCTOATE,MALEIC ANHYDRIDE. May produce an allergic reaction.

### EU DIRECTIVES

System of specific information relating to Dangerous Preparations. 2001/58/EC. Dangerous Preparations Directive 1999/45/EC.

## 16 OTHER INFORMATION

REVISION DATE 29/05/2008

REV. NO./REPL. SDS GENERATED 1

### RISK PHRASES IN FULL

R10	Flammable.
R20	Harmful by inhalation.
R22	Harmful if swallowed.
R36/38	Irritating to eyes and skin.
R40	Limited evidence of a carcinogenic effect.
R51/53	Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

## CRYSTIC 356PA

### DISCLAIMER

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.