

CRYSTICROOF TOPCOAT GREY 6162

SPECIAL FIRE FIGHTING PROCEDURES

Use pressurised air mask if product is involved in a fire. Cool containers exposed to flames with water until well after the fire is out.

UNUSUAL FIRE & EXPLOSION HAZARDS

Fire causes formation of toxic gases.

PROTECTIVE MEASURES IN FIRE

Self contained breathing apparatus and full protective clothing must be worn in case of fire.

6 ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS

Wear protective clothing as described in Section 8 of this safety data sheet.

ENVIRONMENTAL PRECAUTIONS

Spillages or uncontrolled discharges into watercourses must be IMMEDIATELY alerted to the Environmental Agency or other appropriate regulatory body.

SPILL CLEAN UP METHODS

Keep combustibles away from spilled material. Extinguish all ignition sources. Avoid sparks, flames, heat and smoking. Ventilate. Absorb in vermiculite, dry sand or earth and place into containers. Wash thoroughly after dealing with a spillage.

7 HANDLING AND STORAGE

USAGE PRECAUTIONS

Keep away from heat, sparks and open flame. Avoid spilling, skin and eye contact. Ventilate well, avoid breathing vapours. Use approved respirator if air contamination is above accepted level. Vapours are heavier than air and may spread near ground to sources of ignition.

STORAGE PRECAUTIONS

Flammable/combustible - Keep away from oxidisers, heat and flames. Store in tightly closed original container in a dry, cool and well-ventilated place. Keep in original container. Avoid contact with oxidising agents.

STORAGE CLASS

Flammable liquid storage.

8 EXPOSURE CONTROLS/PERSONAL PROTECTION

Name	Std	TWA - 8 hrs		STEL - 15 min		Notes
STYRENE	WEL	100 ppm	430 mg/m3	250 ppm	1080 mg/m3	

WEL = Workplace Exposure Limit.

INGREDIENT COMMENTS

WEL = Workplace Exposure Limits

PROTECTIVE EQUIPMENT



PROCESS CONDITIONS

Provide eyewash station.

ENGINEERING MEASURES

Provide adequate ventilation, including appropriate local extraction, to ensure that the defined workplace exposure limit is not exceeded. All handling to take place in well-ventilated area.

RESPIRATORY EQUIPMENT

Provide adequate ventilation. Observe Workplace Exposure Limits and minimise the risk of inhalation of vapours. At work in confined or poorly ventilated spaces, respiratory protection with air supply must be used. Wear mask supplied with: Gas cartridge suitable for organic substances.

HAND PROTECTION

Use protective gloves made of: Neoprene. Nitrile. Rubber (natural, latex).

EYE PROTECTION

Wear splash-proof eye goggles to prevent any possibility of eye contact.

OTHER PROTECTION

Wear appropriate clothing to prevent any possibility of skin contact.

HYGIENE MEASURES

DO NOT SMOKE IN WORK AREA! Wash at the end of each work shift and before eating, smoking and using the toilet. Promptly remove any clothing that becomes contaminated. Use appropriate skin cream to prevent drying of skin. When using do not eat, drink or smoke.

CRYSTICROOF TOPCOAT GREY 6162**9 PHYSICAL AND CHEMICAL PROPERTIES**

APPEARANCE	Viscous liquid
COLOUR	Grey
ODOUR	Solvent.
SOLUBILITY	Insoluble in water
BOILING POINT (°C)	50-150
RELATIVE DENSITY	1.10 - 1.20 25°C
FLASH POINT (°C)	32 CC (Closed cup).

10 STABILITY AND REACTIVITY

STABILITY

Stable under normal temperature conditions.

CONDITIONS TO AVOID

Avoid exposure to high temperatures or direct sunlight.

HAZARDOUS POLYMERISATION

May polymerise.

MATERIALS TO AVOID

Alkali metals. Strong oxidising substances. Strong acids. Strong alkalis. Organic peroxides/hydroperoxides. Inorganic peroxides.

HAZARDOUS DECOMPOSITION PRODUCTS

Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapours.

11 TOXICOLOGICAL INFORMATION

GENERAL INFORMATION

Prolonged and repeated contact with solvents over a long period may lead to permanent health problems.

INHALATION

In high concentrations, vapours may irritate throat and respiratory system and cause coughing. Harmful by inhalation.

INGESTION

Gastrointestinal symptoms, including upset stomach.

SKIN CONTACT

Acts as a defatting agent on skin. May cause cracking of skin, and eczema. Irritating to skin. Harmful in contact with skin.

EYE CONTACT

Irritating and may cause redness and pain.

12 ECOLOGICAL INFORMATION

ECOTOXICITY

The product is not expected to be hazardous to the environment.

13 DISPOSAL CONSIDERATIONS

GENERAL INFORMATION

Waste to be treated as controlled waste. Disposal to licensed waste disposal site in accordance with local Waste Disposal Authority.

DISPOSAL METHODS

Dispose of waste and residues in accordance with local authority requirements. Make sure containers are empty before discarding (explosion risk). Absorb in vermiculite or dry sand, dispose in licensed hazardous waste.

14 TRANSPORT INFORMATION

UK ROAD CLASS	3
PROPER SHIPPING NAME	RESIN SOLUTION
UN NO. ROAD	1866
UK ROAD PACK GR.	III

CRYSTICROOF TOPCOAT GREY 6162

ADR CLASS NO.	3
ADR CLASS	Class 3: Flammable liquids.
ADR PACK GROUP	III
HAZARD No. (ADR)	30
ADR LABEL NO.	3
HAZCHEM CODE	3Y
CEFIC TEC(R) NO.	30GF1-I+II, 30GF1-sp
RID CLASS NO.	3
RID PACK GROUP	III
UN NO. SEA	1866
IMDG CLASS	3
IMDG PAGE NO.	3
IMDG PACK GR.	III
EMS	F-E, S-E
MFAG	See Guide
MARINE POLLUTANT	No.
UN NO. AIR	1866
AIR CLASS	3
AIR PACK GR.	III

15 REGULATORY INFORMATION

LABELLING



Harmful

CONTAINS

STYRENE

RISK PHRASES

R10	Flammable.
R20	Harmful by inhalation.
R36/38	Irritating to eyes and skin.

SAFETY PHRASES

S24/25	Avoid contact with skin and eyes.
S26	In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
S37	Wear suitable gloves.
S51	Use only in well-ventilated areas.
S60	This material and its container must be disposed of as hazardous waste.
P14	Contains MALEIC ANHYDRIDE. May produce an allergic reaction.

EU DIRECTIVES

Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC, including amendments.

16 OTHER INFORMATION

REVISION DATE	17/02/2009
REV. NO./REPL. SDS GENERATED	3

CRYSTICROOF TOPCOAT GREY 6162

RISK PHRASES IN FULL

R34	Causes burns.
R10	Flammable.
R20	Harmful by inhalation.
R22	Harmful if swallowed.
R65	Harmful: may cause lung damage if swallowed.
R36/38	Irritating to eyes and skin.
R37	Irritating to respiratory system.
R42/43	May cause sensitisation by inhalation and skin contact.
R66	Repeated exposure may cause skin dryness or cracking.
R51/53	Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R67	Vapours may cause drowsiness and dizziness.

DISCLAIMER

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.